

RESIDENTIAL LINE

Mono-Split Air Conditioning Console TOPSMART

A+++



The TOPSMART Console is ideal for every kind of room, since it can be floor and wall-mounted, or installed built-in the wall itself. The easy filter access allows for an easy and effective maintenance and clean-up. The TOPSMART usage is very user-friendly, due to its built-in Wi-Fi.

To better understand this symbols refer to page 9.



* 3 years full warranty + 2 years warranty only parts

TOPSMART Console Units			TOP09 GA	TOP12 GA	TOP18 GA
Cooling	Cooling Capacity	kW	2.7	3.5	5.2
	Input Power	W	720	1000	1550
	Current Input	A	3.5	4.5	7.1
	SEER	W/W	7.2	7.0	6.6
	Energy Class		A++	A++	A++
Heating	Heating Capacity	kW	2.9	3.8	5.3
	Input Power	W	730	960	1500
	Current Input	A	3.6	4.3	6.7
	SCOP	W/W	5.3	5.3	5.3
	Energy Class		A+++	A+++	A+++
Temperature Range IU		°C	16~30	16~30	16~30
Temperature Range OU (Heating/Cooling)		°C	-15~43/-22~24	-15~43/-22~24	-15~43/-22~24
Power Supply (OU)			220-240V-50Hz, 1Ph		
Electrical Connections	Supply	mm ²	3x2,5 (Outdoor unit)	3x2,5 (Outdoor unit)	3x2,5 (Outdoor unit)
	In/Out	mm ²	4x1,5		
Compressor Type			DC INVERTER ROTARY		
Indoor Unit Air Flow		m ³ /h	250~500	280~600	320~700
Noise Level IU (Max/Med/Min)		dB(A)	39/30/23	44/35/25	47/39/31
Indoor unit	Dimensions (WxDxH)	mm	700x215x600	700x215x600	700x215x600
	Unit's Weight	Kg	15.5	15.5	15.5
	Package Dim. (WxDxH)	mm	788x283x697	788x283x697	788x283x697
Outdoor Unit Air Flow		m ³ /h	1600	2200	3200
Noise Level OU		dB(A)	49	52	57
Outdoor unit	Dimensions (WxDxH)	mm	782x320x540	842x320x596	965x396x700
	Unit's Weight	Kg	29	31	46
	Package Dim. (WxDxH)	mm	823x358x595	881x363x645	1029x458x750
Additional Gas Load		g/m	16	16	20
R32 Refrigerant Gas Load (up to 5m)		g	550	750	950
Connections Refrigerant	Liquid/Gas Line	in.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"
	Line Max Length	m	20	20	25
	Line Max Height Dif.	m	10	10	10
Code			NI0115609	NI0115612	NI0115618